



Tron 40S MkII



www.jotron.com



► Tron 40S MkII

Float free and manual GMDSS EPIRB. With new state of the art technology. New non hazardous battery and improved visibility when activated. Fits existing brackets.

SPECIFICATIONS

TECHNICAL	
Battery:	Lithium metal, 7,2V/7200 mAh, 5 years service life
Dimensions:	
• Height:	379 mm
• Diameter:	180mm
Weight:	2 Kg
Materials:	Glass-reinforced Polycarbonate
Compass safe distance:	1.5m
Temperature range:	-20°C to + 55°C (operating) -30°C to +65°C (storage)
Operating life:	Minimum 48 hours at -20°C
Antenna:	Omni directional
Cospas-Sarsat Transmitter	
• Frequency:	406.037 MHz
• Output power:	5W
Homing transmitter	
• Frequency:	121.500 MHz
• Output power:	Up to 100 mW
Protocols:	Maritime, Serialized, Radio Call sign
ACCESSORIES	
Brackets:	Float-free: FB-6
Float-free with heating:	FBH-4
Battery:	Replacement kit
Hydrostatic release:	HRU kit
WARRANTY	
	5 years



Agent/Distributor:

Jotron AS reserves the right to change the design and/or specifications at any time without prior notice. Reservations are also taken towards any general errors that may occur.

v.D

www.jotron.com

CONTACT INFORMATION

Jotron AS
P.O.Box 54
3281 Tjodalving
Norway
Tel: +47 33 13 97 00
Fax: +47 33 12 67 80
sales@jotron.com

Jotron UK Ltd.
Crosland Park
Cramlington
NE23 1LA
United Kingdom
Tel: +44 (0) 1670 712000
Fax: +44 (0) 1670 590265
sales@jotron.com

Jotron Asia Pte. Ltd.
19 Loyang Way
Changi Logistics Centre
Rear Office Block 04-26
Singapore 508724
Tel: +65 65426350
Fax: +65 65429415
sales@jotron.com

Jotron USA, Inc.
10645 Richmond Avenue, Suite 170
Houston, TX 77042
USA
Tel: +1 713 268 1061
Fax: +1 713 268 1062
sales@jotron.com