

# IsatDock2 PRO

## ISD2 PRO

---

LAND Solutions



# IsatDock2 PRO ISD2 PRO



Beam IsatDock2 PRO is an intelligent docking station for the IsatPhone 2 handset\* specifically designed to support accessing voice services via Bluetooth, POTS/RJ11, handsfree speakerphone or the active privacy handset attached to the unit.

IsatDock2 PRO allows the IsatPhone 2 handset to be used in a wide variety of applications. The intelligent POTS/RJ11 interface enables cable runs of up to 600m to connect standard corded, cordless or DECT handsets to be used or alternatively interfaced with a PABX system presenting standard ring, busy and dial tones like a standard phone network.

The IsatPhone 2 handset, fits securely in the dock, its features include phone charging, USB data port, in-built ringer and allows antenna and power to be permanently connected to the dock ready for use.

The IsatDock2 PRO supports Personal Alert, Assistance Button and Tracking functionality of the IsatPhone 2 handset whilst docked.

The IsatPhone 2 handset is easily inserted and removed by the press of a button on the top of the dock making it very easy to use away from the dock when required.

The IsatDock2 Adapter\*\* has been designed to Inmarsat specifications to enhance docking mechanism for the IsatPhone 2 handset. It ensures no wear and tear on USB or audio connectors and has a dedicated compartment on the dock when not in use.

*\* IsatPhone 2 handset sold separately.*

*\*\* 2 adapters are supplied with every IsatDock2*

## KEY FEATURES

- High quality all in one design
- Bluetooth connectivity, via IsatPhone 2 handset
- RJ11 POTS interface, cable runs up to 600m/2000ft
- Dedicated Privacy Handset
- Voice, SMS, SBD and Circuit Switched Data capable
- Tracking and SOS (via the IsatPhone 2 handset)
- USB data interface
- Accessory/Ignition sense
- 10-32V DC power input
- AC Plug pack included 110/240 input
- Supports Active and Passive Inmarsat antennas
- 2 year repair or replacement warranty



data



voice



pots/rj11



pabx  
integration



speaker  
phone



handsfree



privacy



tracking



docking



charging



mute



usb/data  
access



personal  
alert

## Technical Specifications

### POWER SPECIFICATIONS

| Average Power Consumption Current @ 12V | Average | Watts |
|---|---------|-------|
| Power w/o IsatPhone 2                   | 130mA   | 1.6W  |
| Standby + Charging                      | 360mA   | 4.3W  |
| Transmit + Charging                     | 875mA   | 10.5W |
| Sleep Mode                              | 5mA     | 60mW  |
| Peak Current                            | 3.5A    | 42W   |

### ENVIRONMENT SPECIFICATIONS

| Temperature       | Degrees °C | Degrees °F  |
|-------------------|------------|-------------|
| Operating Range   | -30 to +70 | -22 to +158 |
| Storage           | -35 to +85 | -31 to +185 |
| Battery Charging* | 0 to +45   | 32 to +113  |
| Humidity          | <= 75% RH  |             |

### CONNECTORS/INTERFACES

|                      |   |
|----------------------|---|
| POTS/RJ11            | RJ11/2-wire, 5REN @ 600m, Adjustable dial, ring, busy tone configured frequency and adaptive impedance. |
| Antenna              | TNC-Female  |
| GPS Antenna          | SMA-Female  |
| 10-32 VDC            | 4-way microFit (AC/DC adapter, or DC lead)  |
| Privacy Handset Port | RJ9 connector   |
| Configuration / Data | USB Micro   |
| Speakerphone         | In-built speaker/microphone   |
| LEDs/Buttons         | Status LED, Track/Personal Alert, Mute, Up, Down and Speakerphone                                       |

### PHYSICAL SPECIFICATIONS

| Dimensions | mm              | inches          |
|------------|-----------------|-----------------|
| Dock       | 245 x 197 x 100 | 9.6 x 7.7 x 3.9 |
| Outer Box  | 330x 190 x 230  | 13 x 7.5 x 9.1  |
| Weight     | kgs             | lbs             |
| Dock       | 1.45            | 3.19            |
| Box        | 2.45            | 5.39            |

### CERTIFICATIONS

|                        |
|------------------------|
| Inmarsat Type Approval |
| EMC Compliance         |
| FCC                    |
| CE Compliance          |
| Electrical Safety      |
| RoHS                   |
| Industry Canada        |
| C-Tick                 |

### KIT CONTENTS

|                                 |
|---------------------------------|
| IsatDock2 PRO                   |
| 2 x IsatDock2 Adapters          |
| 10-32 DC Power Cable            |
| 110-240V AC Plug Pack           |
| Privacy Handset                 |
| Wall mounting plate             |
| User Manual & Quick Start Guide |

\* It is ideal for the ambient temperature to be approximately 18 degrees below the 45°C upper limit for the handset to charge the battery whilst docked.

## Accessories

|        |   |
|--------|---|
| RST410 | Man Down Kit  |
| ISD960 | IsatDock2 Adapter                                       |
| ISD700 | Fixed/Directional Antenna Passive                       |
| ISD710 | Mast/Pole Marine Antenna Active                         |
| CVTINM | Inmarsat Covert Antenna                                 |
| ISD932 | IsatDock/Oceana SMA/TNC Cable Kit Active - 6m/19.7ft    |
| ISD933 | IsatDock/Oceana SMA/TNC Cable Kit Active - 13m/42.7ft   |
| ISD934 | IsatDock/Oceana SMA/TNC Cable Kit Active - 18.5m/60.9ft |
| ISD935 | IsatDock/Oceana SMA/TNC Cable Kit Active - 31m/101.7ft  |
| ISD938 | IsatDock/Oceana SMA/TNC Cable Kit Active - 40m/131.2ft  |

|        |   |
|--------|---|
| ISD942 | IsatDock/Oceana SMA/TNC Cable Kit Active - 50m/164.0ft  |
| ISD943 | IsatDock/Oceana SMA/TNC Cable Kit Active - 60m/196.85ft |
| ISD944 | IsatDock/Oceana SMA/TNC Cable Kit Active - 70m/229.7ft  |
| ISD945 | IsatDock/Oceana SMA/TNC Cable Kit Active - 80m/262.5ft  |
| ISD946 | IsatDock/Oceana SMA/TNC Cable Kit Active - 90m/295.3ft  |
| ISD947 | IsatDock/Oceana SMA/TNC Cable Kit Active - 100m/320.1ft |
| ISD936 | IsatDock SMA/TNC Cable Kit Passive - 10m/32.8ft         |
| ISD940 | IsatDock SMA/TNC Cable Kit Passive - 40m/131ft          |
| ISD941 | IsatDock SMA/TNC Cable Kit Passive - 50m/164ft          |
| RST060 | UPS Battery Pack  |



Remote Farm/Communities



Recreational Vehicles/Motor Homes



In-Building - PABX Integration



Mining Sites





## Global Head Office (Australia)

---

Beam Communications Pty Ltd ABN 97 103 107 919  
5/8 Anzed Court, Mulgrave, Victoria  
AUSTRALIA 3170

**Tel:** +61 3 8588 4500

**Fax:** +61 3 9560 9055

**Website:** [www.beamcommunications.com](http://www.beamcommunications.com)

**General:** [info@beamcommunications.com](mailto:info@beamcommunications.com)

**Support:** [support@beamcommunications.com](mailto:support@beamcommunications.com)

**Sales:** [sales@beamcommunications.com](mailto:sales@beamcommunications.com)

## Europe

---

**Tel:** +44 208 144 1405

**Fax:** +44 208 289 3542

## United States

---

**Tel:** +1 800 250 5819 (USA toll free)

**Fax:** +1 888 972 8037

APPROVED BEAM RESELLER

© 2016 Beam Communications Pty Ltd

ISD2PRC\_REV02\_11/16