

# **Gyrocompass TG-8100/8600**

TG-8100/8600 is designed based on our previous TG model which has been installed on approximately 27,000 ships, keeping its high reliability, enhanced follow-up performance and interfacing features for equipment. The TG-8000 Series is designed for standard IMO ship application whereas the TG-8600 is designed for High-Speed Craft application.



#### **Features**

- Suitable for speeds of up to 70knots (TG-8600)
- Fast follow-up rate (maximum 75%)
- Fast serial data output (IEC61162-2)
- Interfaces with external heading sensor.
- Minimal system components for dual gyro system for space saving & installation cost.
- Startup-timer function
- Alert transfer feature for BAMS (Bridge Alert Management System) is equipped as standard.

TG-8100: IMO regulated vessels IMO A424 (XI) ISO 8728

TG-8600: High Speed Craft

IMO A821 (19) ISO 16328 HSC



Mass: 23 kg (TypeD)

Unit:mm

#### **Configurations** Control unit Master compass FORE 2-φ13 MOUNTING HOLES 2-φ13 MOUNTING HOLES 20 260 0 340 Φ 486 521 561 4-10×30 MOUNTING HOLES 360 420 455 495 320 340 Ф 0 Mounting dimensions 88 70 438 161.5 3.2 374 3.2 161.5 363.5 467

Mass: 16 kg (TypeS)

General Specifications	Main Power Supply Emergency Power Supply		AC 100 / 110 / 115 / 220 V 1 φ 50 / 60 Hz  DC 24 V  Max.140 VA  Max. 70 VA			
					Power Consumption Starting Operating	
		Repeaters				
	Output Signal				DC 24 V Stepper, 4 Repeaters IEC61162-1ed.2 or IEC61162-2 10 Ports	
			$-10\mathrm{V}\sim+10\mathrm{V}$ / $120^\circ$ or $300^\circ$ / min $3$ Ports			
			Dry Contact (Operation,Alarm)			
	Intput Signal		Speed	200 or 400 Pulses / nm ( Dry contact )		
				IEC61162-1		
			Position ( GPS )	IEC61162-1		
			External Heading Input	IEC61162-1 or IEC61162-2 ( Option )		
				Dry Contact ( Alarm Ack, Buzzer Stop )		
	Performance Specifications	Setting Accuracy	Setting Time	Less than 4 hours		
			Setting Point Error	Less than $\pm$ 0.3°		
		RSM Value	Less than 0.1°			
		Repeatability	Less than ± 0.2°			
Accuracy on Scorsby Table		Less than ± 0.5°				
Master-compass follow up rate		Maximum 75°/s				
	Accuracty Under Environmental Variation		Less than $\pm$ 0.5° ( Condition : ISO8728 / ISO16328 )			
Environmental Conditions	Permissible Roll and Pitch angle		± 45°			



Design and specifications are subject to change without prior notice, and without any obligation on the part of the manufacturer.



Before operating this equipment, you should first throughly read the operator's manual.

# TOKYO KEIKI INC.

## www.tokyokeiki.jp/e/products/marine/

### Marine Systems Company

Head Office 2-16-46, Minami-Kamata, Ohta-ku, Tokyo Tel. +81-3-3737-8611 Fax. +81-3-3737-8663

144-8551 JAPAN

Mass: 23 kg

TOKYO KEIKI (SHANGHAI) CO., LTD. C-1506, Orient International Plaza. Tel. +86-21-3223-1252 Fax. +86-21-6278-7667

No.85 Lou Shan Guan Rd., Shanghai 200336. CHINA

TOKYO KEIKI U.S.A., INC. 3452 E. Foothill Blvd. Suite 420 Pasadena, Tel. +1-626-403-1500 Fax. +1-626-403-7400

CA 91107 U.S.A.